

3M™ Wind Surface Protection Tape W8600, Colorless

Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Product Description

3M™ Wind Surface Protection Tape W8600 provides a simple, easy method of protecting a surface from corrosion, abrasion and minor impact damage.

It is transparent and is made from a tough, abrasion-resistant polyurethane elastomer that resists puncture, tearing, and erosion. This durable material has also been designed to be resistant to UV light.

It can be installed in a minimum amount of time with simple tools. It can be painted or applied over painted surfaces. 3M Wind Surface Protection Tape W8600 is constructed with a long-aging, solvent resistant, pressure sensitive acrylic adhesive that is protected with an easy release poly liner.

Typical Physical Properties

Properties		Typical Values
Approximate Applied Thickness ¹ Inches (mm)	Film	0.006 (0.15)
	Adhesive	0.002 (0.05)
	Total Thickness	0.008 (0.20)
Standard Roll Length ²		36 yd (32.9 m)
Available Widths ² Inches (mm)	Minimum	.25 (6.35)
	Maximum	48.0 (1,219)
Approximate Weight		0.41 lb/yd ² (223 g/m ²)
Splices		Yes

¹ Excludes the liner that is removed from the tape prior to application.

² Custom roll lengths and widths available.

Properties	Test Method	Typical Values
Tensile Strength @ Break lb/in (N/100 mm)	ASTM D882	48 (842)
Elongation % @ Break	ASTM D882	500
Maximum Service Temperature °F (°C)		-40 (-4) to 180 (82)

Safety and Regulatory

- 3M Wind Surface Protection Tape W8600 is 100% solids and contains no hazardous air pollutants (HAPs) or volatile organic compounds (VOCs). Respiratory protection is not required under normal use conditions.
- 3M Wind Surface Protection Tape W8600 and packaging materials meet US Federal and California regulations for landfillable materials. The product is potentially recyclable.
- This product is considered to be an article that does not release or otherwise result in exposure to a hazardous chemical under normal use conditions.

Shipping and Storage

No special/hazardous labeling or packaging required for air, ground or water shipment of this product.

Keep film in a clean area, away from excessive moisture and out of direct sunlight. Store rolls in the shipping carton. Return partially used rolls to the shipping carton.

Shelf life

Two years from date of manufacture.

Precautionary Information

Refer to Material Safety Data Sheet for health and safety information before using this product. For additional health and safety information, visit www.3M.com/msds or call 1-800-364-3577 or (651) 737-6501.

For more information on our wind manufacturing product line, contact 3M Renewable Energy at 800-755-2654 or visit us at www.3M.com/wind.

Technical Information: The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Product Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty, Limited Remedy, and Disclaimer: Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



Renewable Energy Division

3M Center, Building 235-1S-67
St. Paul, MN 55144-1000
1-800-755-2654
www.3M.com/wind

Please recycle. Printed in USA.
Issued: 1/10 © 3M 2010.
All rights reserved. 7158HB
98-0150-0079-1

3M is a trademark of 3M Company.
Used under license by
3M subsidiaries and affiliates.